

Scotchkote Electrical Coating

1. Product Description

"Scotchkote" Brand Electrical Coating is a fast drying sealant and bonding agent recommended for joints wrapped with plastic electrical tape. The product is supplied in a 15 ounce brush top can.

Product Features

- Compatible with "Scotch" Brand Plastic Electrical Tapes.
- Fast drying -Flexible when dry
- Contains own applicator
- No waste if container resealed after use.

2. Applications

"Scotchkote" Brand Electrical Coating is intended for use as an outer seal on plastic tape applications which are subjected to excessive amounts of oil. It also improves the weather resistance and moisture resistance of the taped joint or splice. It is suitable for direct burial, direct water immersion or above ground applications.



Precautionary and first aid information for this product may be found in its Material Safety Data Sheet and on the product container.

3. Data

Physical Properties		
Property		Result
Oil-Proof Test (ASTM)		Passed
Adhesion to	- Wood	Good
	- Metal	Good
	- Rubber	Good
	- Plastic	Good
Dielectric Strength		
Dry -----		450 volts/mil
24 hrs. in H2O		200 volts/mil
Chemical Structure		
Property		Typical Value
Solvent		Methyl ethyl ketone, toluene
Solids (25%)		Synthetic rubber & resin
Flash Point		+30°F/-1°C
Applicable Specification		
MIL-P-18623		

4. Application Techniques

After taping splices with "Scotch" Brand Vinyl Plastic Electrical Tape, apply "Scotchkote" Brand Electrical Coating evenly over splice, extending a short distance onto the cable insulation. Be sure the surface is clean, dry and free from oil or grease before electrical coating is applied.

5. Availability

"Scotchkote" Brand Electrical Coating is available in a 16 oz. can size with 10 cans per case and may be purchased from your local electrical distributor.

IMPORTANT NOTICE TO PURCHASER:

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

All statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.
© 3M 1993

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECTOR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.